

Made to Order Common Specifications:

-XC65: Made of Stainless Steel (Combination of XC7 and XC68)



48 Made of Stainless Steel (Combination of XC7 and XC68)

Symbol

-XC65

Suitable for the cases it is likely to generate rust by being immersed in the water and corrosion.

Applicable Series

| Series | Description | Model | Action | Note | Vol. no. (for std model) |
|------------|--------------------|--------|---------------------------|-------------|--------------------------|
| MB | Air cylinder | MB-Z | Double acting, Single rod | Except ø125 | Web Catalog |
| | Smooth cylinder | MBW-Z | Double acting, Double rod | Except ø125 | |
| MB1 | Air cylinder | MB1-Z | Double acting, Single rod | Except ø125 | |
| | | MB1W-Z | Double acting, Double rod | Except ø125 | |
| | | CA2-Z | Double acting, Single rod | | |
| CA2 | Air cylinder | CA2W-Z | Double acting, Double rod | | |
| | | CA2H | Double acting, Single rod | | |
| | Air-hydro cylinder | CA2HW | Double acting, Double rod | | |
| | | CA2Y-Z | Double acting, Single rod | | |
| | Smooth cylinder | | | | |

Specifications

| | |
|----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Parts changed to stainless steel | Tie-rod, Tie-rod nut, Bracket mounting nut, Spring washer, Cushion valve, Retaining ring, Piston rod (with hard chrome plated), Rod end nut |
| Maximum manufacturable stroke (mm) | Double acting, Single rod: 1600 Double acting single rod with rod boot: 1000 |
| Specifications other than above and external dimensions | Same as standard type |

How to Order

Standard model no.

– XC65

Made of stainless steel
(Combination of XC7 and XC68)